









Telecamere HD PTZ

Caratteristiche: HD/TVI/CVI/CVBS + PAL/NTSC (Tramite DIP Switch), privacy mask, ICR auto/day/night, Noise reduction, motion detection, IP66.

	I5PT-390AX4	I5PT-390AX10
		
Risoluzione	2 MP	2 MP
Ottica	4X (2,8-12mm)	10X (5,1-52mm)
Pan/Tilt range	250° horizontal - 65° vertical	250° horizontal - 65° vertical
Distanza IR	50m (IR LED ARRAY)	50m (IR LED ARRAY)
Alimentazione	DC12V/2A	DC12V/2A

	MZ-10A-2(IR)	ZE-20A-2(IR)	ZP-20A-2(IR)
			
Risoluzione	2 MP	2 MP	2 MP
Ottica	x10 (4,7-47mm)	20X(4,9-97mm)	20X (4,9-97mm)
Pan/Tilt range	360° (Endless)/180° (Auto Flip)	360° (Endless)/180° (Auto Flip)	360° (Endless)/180° (Auto Flip)
Distanza IR	60m IR LED	100m IR LED Array	100m IR LED Array
Alimentazione	DC12V/2A	12VDC/2A	124VAC/3A
Staffe/box di giunzione	vedi tabella sotto	vedi tabella sotto	vedi tabella sotto

IP - HD / Staffe PTZ e Speed Dome

		
staffa da soffitto	staffa da palo	staffa da angolo
		
		
staffa da angolo interno		staffa da soffitto per modelli MZ
