



## Telecamere ULTRA 2 MP



**Caratteristiche:** HD/TVI/CVI/CVBS + PAL/NTSC (Tramite DIP Switch), 25/30 fps, True Day&Night-ICR, True WDR, BLC, 3D-DNR, Privacy mask, S/N Ratio  $\geq 52$ dB (AGC OFF), Bilanciamento bianco (Auto, Manuale), Supporto CoC, Menu OSD (tramite CoC), IP 67.

DI-320AU-MVF | DI-320AU-MVF-G



DAI-320AU-VF



I4-320AU-MVF



	DI-320AU-MVF   DI-320AU-MVF-G	DAI-320AU-VF	I4-320AU-MVF
Ottica	2.8-12mm Motorized Vari-Focal (96°-34°)	2.8-12mm Vari-Focal ( 88°-33° )	2.8-12mm Motorized Vari-Focal (96°-34°)
Sensore immagine	1/2.8" 2MP Sensor	1/2.9" 2MP Sensor	1/2.8" 2MP Sensor
Distanza IR	3 LED Array (40m)	3 LED Array (40m)	2 LED Array (40m)
Alimentazione	DC12V/660mA	DC12V/660mA	DC12V/620mA
Staffe/box di giunzione	F	H	B

IP HD / Staffe/box di giunzione per telecamere

**A - Bullet I2**



**B - Bullet I4**



**C - Bullet I6**



**D - Fisheye**



**E - Mini dome**



**F - Turret/Dome vari-focal**



**G - Turret/Dome ottica fissa**



**H - Anti-vandal dome vari-focal**



**I - Anti-vandal dome ottica fissa**



**L - Intelligent Auto-Tracking PTZ**

